



# HUBBLE

LITHIUM BATTERY

ADVANCED ENERGY  
STORAGE SYSTEMS



## HUBBLE LITHIUM - AM-2 51V 5.5KW

- Advanced BMS with current limiting function
  - CAN Bus, fully integrates and communicates with leading Inverter brands
  - Excellent high temperature performance
  - High Cycle Life and Service Life
  - RIOT integration ready for cloud monitoring
  - Advanced LCD display with battery state, voltage, cycles, etc.
  - High Energy Density and conversion efficiency
  - Complete with integrated Battery Management System
  - Compatible with most Inverters and chargers
  - Low self discharge
  - Easy wall mount or shelf rack installation
  - Heavy duty side handles for easy handling and mounting on the wall
  - Built in protection for over-charge, over-discharge & over-temperature



APPROVED BATTERY

ITEM	SPECIFICATION		
Model	Hubble AM-2		
Rated Capacity (5HR)	100 Ah		
Nominal Voltage	51.0 V		
Discharge Cutoff Voltage	42.0 V		
Equilized Charge Voltage	54.0 V		
Max. Continuous Charging Current	100 A		
Max. Continuous Discharging Current	100 A		
C Rating	1.0 C		
Weight	Approx. 42 Kg		
Display	None		
Parallel	Parallel connection up to 15 packs with full communications		
Dimensions (WxDxH) mm	375mm x 145mm x 467mm		
Ports	1x CAN-bus, 2x RS-485, 1x RS232		
Cells	New BYD Li-ion Cells		
Cycle Life @ 1C	+/- 3 000 Cycles with 80% battery life left		
Certification	CE, UN38.3, GBT31484-2015, GBT31485-2015, GBT31486-2015		
Outer Package Material	White bake lacquer steel case		
Operating Temperature	Charging: 0 to +55°C	Discharging: -20 to +55°C	Storage: -20 to +55°C
Protection	Electronic Circuit Breaker, BMS Voltage Protection, Current Limiting		

\* Due to continuous product improvements, specifications are subject to change without further notice.

All products are manufactured to the following standards:



ADVANCED ENERGY  
STORAGE SYSTEMS

