



SUNSYNK-L5.1



DATASHEET

Room 702-704, 7/F Texwood Plaza, 6 How Ming Street,
Kwun Tong, Kowloon, Hong Kong

Tel: +852 2884 4318 Fax: +8522884 4816

www.sunsynk.com / sales@sunsynk.com



Main Parameter		SUNSYNK-L5.1
Battery Chemistry		Lithium Ferro Phosphate (LifePO4 or LFP)
Capacity		100 Ah
Scalability		Max. 32 pcs in parallel (163.8kWh)
Nominal Voltage		51.2 V
Operating Voltage		43.2~57.6 V
Energy		5.12 kWh
Usable Energy ^[1]		4.61 kWh
Charge/Discharge Current	Recommend ^[2]	50 A
	Max. ^[2]	100 A
	Peak (2mins,25°)	150 A
Other Parameter		
Recommend Depth of Discharge		90%
Dimension (W/H/D)		440*620*135mm (don't include Circuit Breaker, terminals and hanging boards)
Weight Approximate		50kg
Master LED Indicator		5 LED (SOC 20%~100%)
		3 LED (working, alarming, protecting)
IP Rating of enclosure		IP65
Working Temperature		Charge: 0°C ~ +55°C (optional heating: -20°C~+55°C) Discharge: -20°C ~ +55°C
Storage Temperature		-20°C ~ +35°C
Humidity		5% ~ 95%
Altitude		≤2000m
Installation		Wall Mounted or 19-inch standard cabinet
Communication Port		CAN2.0, RS485
Certification		IEC62619, CE, UN38.3

[1] DC Usable Energy, test conditions: 90% DOD, 0.5C charge & discharge at 25°C. System usable energy may vary due to system configuration parameters.

[2] The current is affected by temperature and SOC.



CONTACT US

Email us: sales@sunsynk.com **Call us UK:** +44 151 832 4300

VAT Number: 175669460

UK Address: Sunsynk, 17 Turnstone Business Park,
Mulberry Avenue, Widnes, Cheshire, WA8 0WN.

GlobalTech Ltd



SGS

UK
CA CE

Powered by
SUN SYNK